

SAMPLE CASE

Specification Sheet v1.0

www.heraled.com



Hera LED has practical and complete sample kits for its product lines. They are offered product-wise or as a mix if requested. Sample kits serve as training tools to familiarize yourself with our products and can be used to make demonstrations to your potential customers with Hera LED façade lighting offer. They have their own LED driver (48V DC) and integrated vivid animation scenarios for each product inside. All our Sample Cases are lightweight yet robust and ergonomically they are very easy to use on your travels.



SAMPLE CASE

www.heraled.com

Specifications



Products:	MIX	PD60 SERIES	Chronopix	SWORD SERIES	LEOLINE	MOLELINE	PROCOLOR
Contents:	1 Pcs. PD60 RGB DMX Dome Pixel Dot 2 Pcs. Chronopix@6 RGBW 1 Pcs. Sword@ 300mm RGB Direct View 1 Pcs. Sword@ 300mm RGB Flat Diffused 1 Pcs. Sword@ 300mm RGB Radius Diffused 1 Pcs. Leoline@ S12 315mm DMX RGB Surface Mounted Narrow Beam 15° 1 Pcs. Moleline@ M6 356mm DMX RGBW Inground Narrow Beam 15°	1 Pcs. PD60 RGB DMX Direct View Pixel Dot 1 Pcs. PD60S RGB DMX Direct View Pixel Dot 1 Pcs. PD60 RGB DMX Dome Pixel Dot 1 Pcs. PD60 RGBW DMX Direct View Pixel Dot 1 Pcs. PD60S RGBW DMX Direct View Pixel Dot 1 Pcs. PD60 RGBW DMX Dome Pixel Dot 1 Pcs. PD60 DW DMX Direct View Pixel Dot 1 Pcs. PD60S DW DMX Direct View Pixel Dot 1 Pcs. PD60 DW DMX Dome Pixel Dot	3 Pcs. Chronopix@6 RGB 3 Pcs. Chronopix@6 RGBW 3 Pcs. Chronopix@6 RGBA 3 Pcs. Chronopix@6 DW	1 Pcs. Sword@ RGB 300mm Flat Diffused 1 Pcs. Sword@RGB 300mm Radius Diffused 1 Pcs. Sword@ RGB 300mm Direct View 1 Pcs. Sword@ RGBW 300mm Flat Diffused 1 Pcs. Sword@ RGBW 300mm Radius Diffused 1 Pcs. Sword@RGBW 300mm Direct View 1 Pcs. Sword@DW 300mm Flat Diffused 1 Pcs. Sword@DW 300mm Radius Diffused 1 Pcs. Sword@DW 300mm Direct View	1 Pcs. Leoline@ M6 315mm DMX RGBW Surface Mounted Medium Beam 25° 1 Pcs. Leoline@ S12 315mm DMX RGB Surface Mounted Narrow Beam 15° 1 Pcs. Leoline@ S12 315mm DMX RGBW Surface Mounted Medium Beam 30° 1 Pcs. Leoline@ S12 315mm DMX RGBA Surface Mounted Wide Beam 45° 1 Pcs. Leoline@ S12 315mm DMX RGBA Surface Mounted Wide Beam 60°	1 Pcs. Moleline@ M6 356mm DMX RGBW Inground Medium Beam 25° 1 Pcs. Moleline@ S12 356mm DMX RGB Inground Narrow Beam 15° 1 Pcs. Moleline@ S12 356mm DMX RGBW Inground Wide Beam 45° 1 Pcs. Moleline@ S12 356mm DMX DW Inground	1 Pcs. Procolor@DC 10RGBW Floodlight Medium Beam 25° 1 Pcs. Procolor@DC 10DW Floodlight Medium Beam 25° 1 Pcs. Procolor@DC 60RGBW Floodlight Medium Beam 25° 1 Pcs. Procolor@DC 60DW Floodlight Medium Beam 25° 1 Pcs. Procolor@AC 10SC 90-264 VAC Floodlight Narrow Beam 19° 1 Pcs. Procolor@AC 35SC 90-264 VAC Floodlight Narrow Beam 30° 1 Pcs. Procolor@AC 60SC 90-264 VAC Floodlight Narrow Beam 30°
Connections:	Power cable – Neutrik® PowerCON, UL power cord, universal plug adapter						
Control:	Integrated animation software on/off						
Weight:	12Kg	10Kg	8,3Kg	11Kg	12,5Kg	15Kg	16Kg
Dimension:	220x380x580mm						



Sample Case; Sword®, PD60, Leoline®, Moleline®, Procolor®, Chronopix®, is a HERA LED registered trademark. HERA LED may change the features of the Sample Case and the products in the bag without notice. Please refer to the relevant web page for detailed information about the products in the Sample Case.